

The new SmartDetect ISOMETER® iso415R



The new ISOMETER® iso415R is a reliable and simple insulation monitoring device. It combines easy operation, multiple interfaces, and flexible application options in a compact design.



Simple set up

The parameters of the iso415R can be adjusted easily and quickly either with switches on the unit or with the Bender Connect App.



Compact, space saving size

Narrow width of 18 mm (0.7") means the iso415R requires little space, leaving room for other devices in the control cabinet.



Secure communication

Thanks to the wired Modbus RTU interface, the iso415R can transfer its data to the facility network.



Versatile use

The iso415R can be used with AC or DC circuits in ungrounded systems up to 400 volts.



Simple app control

The Bender Connect app enables easy operation via smartphone over Near Field Communication.

USA • Exton, PA

+1 800.356.4266 • www.benderinc.com

Canada • Missisauga, ON

+1 800.243.2438 • www.bender-ca.com

México • Ciudad de México

+55 7916.2799 • www.bender.com.mx

South America, Central America, Caribbean

+1 484.288.7434 •www.bender-latinamerica.com

Chile • Santiago de Chile

+56 2.2933.4211 • www.bender-cl.com

Spain • San Sebastián de los Reyes

+34 9.1375.1202 • www.bender.es

14.30i.REV.0 | 7.2021 | © Bender Inc. All Rights Reserved.